

ViewSonic® PROJECTOR PJD5155

Key Features



Product Description

The ViewSonic LightStream PJD5155 projector features 3300 lumens, native SVGA 800 x 600 resolution, and intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wider color range for true-to-life image projection, while SonicExpert™ technology delivers improved sound quality. The PJD5155 also features extensive connectivity including HDMI, 2 x VGA, Composite Video, S-Video, 1 x VGA output, Audio in/out, Mini USB and RS232. An energy-saving DynamicEco® feature reduces power consumption by up to 70%, and extends the lamp life by up to 10,000 hours. With advanced audiovisual features, and flexible connectivity options, the PJD5155 is ideal for use in education and small business environments.

Visit Us www.viewsonic.com

DISPLAY

Resolution:	800x600
Lens:	Digital Zoom: 0.8X~2.0X
Size:	30 - 300 inch
Throw Distance:	1.0m - 8.0m
Throw Ratio:	1.86~2.04
Lamp:	190W
Brightness:	3300 ANSI Lumens
Contrast Ratio:	22,000:1 (DynamicEco Mode)
Keystone Correction:	Vertical: +40~-40°, (Manual)
Aspect Ratio:	4:3
Color Depth:	1.07 Billion Colors (30 bits per color)
Optical Offset:	100%+/-5%

AUDIO

Speakers:	2W cube x 1
-----------	-------------

INPUT SIGNAL

Video:	NTSC: NTSC M (3.58 MHz), 4.43MHz PAL: PAL (B, D, G, H, I, M, N, 60) SECAM: SECAM (B, D, G, K, K1, L) SD: 480i and 576i ED: 480p and 576p HD: 720p,1080i, 1080p
Frequency:	Fh: 15-102KHz; Fv: 23-120Hz

COMPATIBILITY

PC:	800x600@60Hz (native)
Mac:	800x600@60Hz (native)

CONNECTOR

RGB Input:	VGA Input x2
RGB Output:	VGA Output x1
Composite Video:	RCA-1 x1
S Video:	Mini-Din 4 pin (x1)
Component Video:	Share with VGA x2
Digital:	HDMI 1.4 x 1
Audio:	3.5mm Mini-Mono Jack (x1)
USB:	Mini USBx1

POWER

Voltage:	100~240Vac 50/60Hz (Auto Switching)
Consumption:	265 W (Max.)

OPERATING CONDITIONS

Temperature:	0°~40°C / 32°~104°F
Humidity:	10~90%, Non-Condensation

DIMENSIONS

Physical:	316mm (width) x 103.7mm (height) x 228mm (depth)
-----------	--------------------------------------------------

WEIGHT

Net:	2.2 kg
------	--------

REGULATIONS

CB, TUV-GS, UL/cUL, FCC (including ICES-003), CE,C-Tick Mexico Energy test/Registration, EAC, UkrSEPRO/EMC DOC, UL COC, TUV-S Mark(Argentina), PSB, KCC, KC, SASO, CCC WEEE, RoHS, REACH, SVHC, ErP

PACKAGE CONTENTS

1. Power Cord, 1.8m; 2. VGA Cable, 1.8m; 3. Remote Control with Batteries (Without Laser); 4. Quick Start Guide (one sheet version), x1; 5. ViewSonic CD Wizard (w User Manual) x 1
